



A Textron Company

2004 Clays Car G PRODUCT SPECIFICATIONS

STANDARD EQUIPMENT:

| | |
|---------------------------|---|
| Engine: | 11.0 H.P. (8.2 KW) Rated, 4 cycle, 21 ci (350 cc) twin cylinder, air cooled, by Robin USA. |
| Valve Train: | Overhead Valve, overhead cam, belt drive. |
| Lubrication: | Pressurized oil system, washable permanent filter. |
| Balancer: | Internal counter rotating balance shaft. |
| Ignition: | Solid State with crank trigger, electronic timing advance, and RPM limiter. |
| Carburetor: | Fixed jet float bowl with remote pulse fuel pump. |
| Air Cleaner: | Replacable dry cartridge |
| Electrical System: | Starter/Generator, solid state regulator, 12 volt maintenance free battery, 430 CCA, 51 minute reserve. |
| Drive Train: | Automatic, continuously variable transmission (CVT) |
| Transaxle: | High efficiency differential with steel helical gears, 13.32:1 ratio, ground speed governor, forward/reverse. |
| Brakes: | Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings. Automatic park brake release with self-compensating system. |
| Front Suspension: | Heavy duty leaf springs with hydraulic shock absorbers. |
| Rear Suspension: | Heavy duty leaf springs with hydraulic shock absorbers. |
| Steering: | Self-compensating single reduction rack and pinion. |
| Seating: | Vacuum formed fabric backed vinyl covers over thick cushion foam. Standard seating for operator and three passengers. |
| Fuel System: | 6.0 gallon (22.8L) tank with analog fuel gauge in instrument panel. |
| Speed: | 14.5 – 15.5 MPH (23 – 25 KPH) |

DIMENSIONAL SPECIFICATIONS:

| | |
|-------------------------------|--|
| Weight: | 960 lbs. (435kg), dry; fuel capacity 31 lbs. (14kg) |
| Length: | 107 inches (2.72 m) Including rear foot rest |
| Width: | 46.5 inches (1.18 m) |
| Height: | 49 inches (1.24 m) (top of steering wheel) |
| Ground Clearance: | 6.0 inches (0.15 cm) (at differential) |
| Wheel Base: | 65.5 inches (1.66 m) |
| Front Wheel Tread: | 38.5 inches (0.98 m) |
| Rear Wheel Tread: | 38.0 inches (0.97 m) |
| Turning Clearance Dia: | 20.3 feet (7.1 m) |
| Tires: | 20 x 10 x 10 Turf Saver (4 ply rated) |
| Load Capacity: | 800 lbs. (363 kg) including operator, passenger, accessories and cargo 250 lbs. (113 kg) max. cargo bed load. |
| Load Bed Size: | 40 inches wide, 32 inches long (102cm x 81cm) |

FEATURES:

| | |
|-------------------------------|--|
| Body: | Flexible impact resistant front and rear cowls. |
| Finish: | Durashield™ powder primer and top coat. |
| Body Protection: | Flexible front fender flair, tubular steel front bumper with brush guards. |
| Chassis: | Welded high yield strength tubular steel with Durashield™ powder coat paint. |
| Safety: | Key switch, reverse warning indicator, "deadman" accelerator control, integral handgrip on hip restraints, manual forward/reverse selector with neutral lock, Dual Halogen Headlights, and Horn. |
| Dash Panel: | Instrument Panel with four drink holders and 12V outlet. Locking Glove Box. |
| Steering Wheel: | Sport Model. |
| Convertible Rear Seat: | Rear seat converts to flatbed. |
| Gun Rack: | Stand up gun holder with positions for 2 shotguns |
| Front Rack: | 9" wide, 37" long, 9" deep (23cm x 94 cm x 29 cm) Steel front storage rack |
| Side Baskets: | Two 9" wide, 7" long, 9" deep (23 cm x 18 cm x 29 cm) Steel side storage rack |

specifications subject to change without notice.