



A Textron Company

2004 E-Z-GO 1200 PRODUCT SPECIFICATIONS

STANDARD EQUIPMENT:

Engine:	11.0 H.P. (8.2KW) rated, 4 cycle, 21 ci (350 cc) twin cylinder, air-cooled, by Robin USA.
Valve Train:	Overhead valve, overhead cam, belt drive.
Lubrication:	Pressurized oil system, washable permanent filter.
Balancer:	Internal counter rotating balance shaft.
Ignition:	Solid State with crank trigger, electronic timing advance, and RPM limiter.
Carburetor:	Fixed jet float bowl with remote pulse fuel pump.
Air Cleaner:	Replaceable dry cartridge with remote air intake.
Electrical System:	Starter/Generator, Solid State Regulator, 12V maintenance free battery, 430 CCA, 60 minute reserve.
Drive Train:	Automatic, continuously variable transmission (CVT).
Transaxle:	High efficiency differential with helical gears, 13.32:1 ratio, ground speed governor, forward and reverse.
Brakes:	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings. Automatic park brake release with self-compensating system.
Front Suspension:	Heavy-duty leaf springs with hydraulic shock absorbers.
Rear Suspension:	Heavy-duty leaf springs with hydraulic shock absorbers.
Steering:	Self-compensating single reduction rack and pinion.
Seating:	Vacuum formed fabric backed vinyl covers over thick cushion foam. Standard seating for operator and one passenger.
Fuel System:	6.0 gallon (22.8L) tank.
Speed:	12.5 – 13.5 MPH (20 – 22 KPH)

DIMENSIONAL SPECIFICATIONS:

Weight:	862 lbs. (391kg), dry; fuel capacity 31 lbs. (14kg)
Length:	110.5 inches (2.8m)
Width:	49.8 inches (1.26m) (outside at bed)
Height:	46.5 inches (1.18m) (top of steering wheel)
Ground Clearance:	4.75 inches (0.12m) (at differential)
Wheel Base:	77 inches (1.96m)
Front Wheel Tread:	37.5 inches (0.95m)
Rear Wheel Tread:	38 inches (0.97m)
Turning Clearance Dia:	22 feet (6.7m)
Tires:	18 x 8.50 x 8 (4 ply rated)
Load Capacity:	1,200 lbs. (544kg) including operator, passenger, accessories, and cargo 800 lbs. (363kg) max. bed load.
Load Bed Size:	45 inches wide, 36 inches long, 13.75 inches deep (114cm x 91cm x 35cm)
Load Bed Volume:	13 cubic feet (0.37 cubic meters)

FEATURES:

Body:	Front: Flexible impact resistant front cowl. Rear: Lightweight, replaceable, steel panels.
Finish:	Durashield™ powder primer and top coat.
Body Protection:	Flexible front fender flair.
Cargo bed:	Rotomolded polybox. Quick release for easy service access. Hinged, removable tailgate.
Chassis:	Welded high yield strength tubular steel with Durashield™ powder coat paint and E-shield.
Safety:	Dash mounted key switch, reverse warning indicator, "deadman" accelerator control, integral handgrip on hip restraints, manual forward/reverse selector with neutral lock, and Horn.
Dash Panel:	Instrument Panel with four drink holders.
Steering Wheel:	Sport Model.