



2004 ST SPORT PRODUCT SPECIFICATIONS

STANDARD EQUIPMENT:

Engine:	11.0 H.P. (8.2 KW) Rated, 4 cycle, 21 ci (350 cc) twin cylinder, air cooled, by Robin USA.
Valve Train:	Overhead Valve, overhead cam, belt drive.
Lubrication:	Pressurized oil system, washable permanent filter.
Balancer:	Internal counter rotating balance shaft.
Ignition:	Solid State with crank trigger, electronic timing advance, and RPM limiter.
Carburetor:	Fixed jet float bowl with remote pulse fuel pump.
Air Cleaner:	Replacable dry cartridge with remote air intake.
Electrical System:	Starter/Generator, solid state regulator, 12 volt maintenance free battery, 430 CCA, 51 minute reserve.
Drive Train:	Automatic, continuously variable transmission (CVT)
Transaxle:	High efficiency differential with steel helical gears, 13.32:1 ratio, ground speed governor, forward/reverse.
Brakes:	Dual rear wheel mechanical drum brakes, self-adjusting with non-asbestos linings. Automatic park brake release with self-compensating system.
Front Suspension:	Heavy duty leaf springs with hydraulic shock absorbers.
Rear Suspension:	Heavy duty leaf springs with hydraulic shock absorbers.
Steering:	Self-compensating single reduction rack and pinion.
Seating:	Vacuum formed fabric backed vinyl covers over thick cushion foam. Standard seating for operator and one passenger.
Fuel System:	6.0 gallon (22.8L) tank with analog fuel gauge in instrument panel.
Speed:	14.5 – 15.5 MPH (23 – 25 KPH)

DIMENSIONAL SPECIFICATIONS:

Weight:	960 lbs. (435kg), dry; fuel capacity 31 lbs. (14kg)
Length:	103 inches (2.62 m)
Width:	46.5 inches (1.18 m)
Height:	49 inches (1.24 m) (top of steering wheel)
Ground Clearance:	6.0 inches (0.15 cm) (at differential)
Wheel Base:	65.5 inches (1.66 m)
Front Wheel Tread:	38.5 inches (0.98 m)
Rear Wheel Tread:	38.0 inches (0.97 m)
Turning Clearance Dia:	20.3 feet (7.1 m)
Tires:	21 x 9 x 10 Work Mate (4 ply rated)
Load Capacity:	650 lbs. (295kg) including operator, passenger, accessories and cargo 250 lbs. (113 kg) max. cargo bed load.
Load Bed Size:	46 inches wide, 35 inches long, 10 inches deep, (117cm x 89cm x 25cm)
Load Bed Volume:	9 cubic feet (0.25 cubic meters)

FEATURES:

Body:	Front: Flexible impact resistant front cowl. Rear: Lightweight, replaceable, steel panels.
Finish:	Durashield™ powder primer and top coat.
Body Protection:	Flexible front fender flair and rear fenders, tubular steel front bumper with brush guards.
Cargo bed:	Heavy duty bed liner with tailgate cover. Hinged, removable tailgate.
Chassis:	Welded high yield strength tubular steel with Durashield™ powder coat paint.
Hitch:	Rear 2 inch receiver.
Safety:	Dash mounted key switch, reverse warning indicator, "deadman" accelerator control, integral handgrip on hip restraints, manual forward/reverse selector with neutral lock, halogen headlights, and Horn.
Dash Panel:	Instrument Panel with four drink holders.
Steering Wheel:	Sport Model.

Specifications subject to change without notice.